

*Sup C*

Application No. 09/482,969

8. (Twice Amended) A method for use in managing an outgoing call comprising the steps of:

placing an outgoing call to a remote party location over a communication network; processing an initial signal received from said remote party location during said call to determine a source type of said initial signal;

playing a prerecorded greeting to said remote party location during said step of processing, wherein said step of playing a prerecorded message includes detecting a period of silence after receipt of said initial signal and initiating playback of said prerecorded greeting in response thereto; and

after said prerecorded greeting has ended, establishing a talk path between a local agent and the remote party location when it is determined that said initial signal is a voice signal that was generated by a live party during the call.

*B3*

9. (Amended) The method claimed in claim 8, further comprising the step of:

terminating the call when it is determined that said initial signal was not generated by a live party during the call.

10. (Amended) The method claimed in claim 8, wherein:

said step of placing an outgoing call includes dialing a telephone number associated with a remote party and said initial signal processed in the processing step is the initial audible signal received during said call.

*B4*  
Application No. 09/482,969

12. (Amended) The method claimed in claim 8, wherein:  
said step of processing a signal includes using a call classifier to determine whether the initial signal  
was generated by a live party during the call.

*B5*  
17. (Amended) The system claimed in claim 15, wherein:  
said external communication network includes a public switched telephone network and said first  
detected signal is received during said call.